

**AMRON INTERNATIONAL - MASTER DISTRIBUTOR**

**SY-240H AMEREX MODEL HYPERBARIC WATER BASED FIRE EXTINGUISHER**



**Features:**

- Maximum visibility during discharge
- Easy to recharge and maintain
- Leaves no powder residue
- Stored Pressure Design
- Polished Stainless Steel Cylinders
- All Metal Valve Construction
- Large Loop Stainless Steel Pull Pin
- Exclusive crevice free, butt welded cylinders

**Model 240H Hyperbaric Water Based Fire Extinguisher: Part Number Model-240H Includes:**

- Fill Adapter
- Wall Hanger
- Owner's Manual

**Specifications:**

- Water Capacity: 2.5 gal. (9.5 liters)
- Maximum Pressure: 200 psi (13.8 bar)
- Maximum Depth: 225 FSW
- Range: 45 – 55 ft.
- Discharge Time: 55 seconds
- Dimensions: 24.5 in. H X 9 in. W X 7 in. D (62.2 cm X 22.8 cm X 17.8 cm)
- Empty Weight: 7.50 lbs. (3.40 kg)
- Temperature Range: 40°F to 120°F (4°C to 49°C)
- Relief Valve
- Outlet relief pressure: 425 PSI
- Inlet relief pressure: 3 PSI (If the fire extinguisher is empty and placed in a chamber, this valve will let pressure in from the environment into the fire extinguisher)

**Conforms to Test Standards:**

- CAN/ULC-S507 - ANSI/UL626
- CAN/ULC-S508 - ANSI/UL711


**Application:**

- Designed for use in manned pressure vessels/ hyperbaric chambers
- Suitable for use in chambers simulating 225 ft. (depth)




**Note: Fire Extinguisher ships empty**



# Contact us

 29th Street, Amman Road, Behind Al Huraiz Est. For Industry,  
Al Qusais, Industrial Area – 1,  
Dubai, United Arab Emirates

-  Tel : 009714 2580533 
-  Fax : 042516664 
-  UAE : 00971505648178 
-  UK : 00447951966260 

-  Website : [www.synergyequipment.com](http://www.synergyequipment.com)
-  Email : [ram@synergyequipment.com](mailto:ram@synergyequipment.com)
-  For Sale : [info@synergyequipment.com](mailto:info@synergyequipment.com)

