



SY-803139-01-02 Pressure Vak II™ - Medium Face Seal without 1st Stage Regulator Assembly without Microphone

## **Features:**

- Quick disconnect face seal allows easy cleaning
- Full head harness for added comfort during long administration
- Exhausts exhaled gases over board, permitting minimum ventilation of the chamber
- Demand Regulator permits constant flow operation
- Demand Regulator designed to operate with constant inlet pressure of 65 to 125 PSI over chamber pressure

## **Specifications:**

• Weight: 4.4 lbs.

## Pressur Vak II<sup>™</sup> - Medium Face Seal without 1st Stage Regulator Assembly without Microphone -P/N: 803139-01-02 Includes:

- (1) SY-18969-00 Oxygen Cleaned Quick Disconnect Socket-P/N:
- (1) SY-59853-00 Exhaust Quick Disconnect Socket
  - P/N
- (1) SY-803139-UM AVOX User Manual P/N:

803115-01

800956-0

26010-0

303152-XX (XX = Size)

21506-01

13796-00

18062-00

Doa

2827-49

26018-01

801272-00

803166-10

26037-10

59719-10

801275-00

803100-01

1000257;





## **Contact us**



29th Street, Amman Road, Behind Al Huraiz Est. For Industry,
Al Qusais, Industrial Area – 1,
Dubai, United Arab Emirates

Tel

Fax : 042516664

: 009714 2580533

- UAE : 00971505648178 🗖
- UK : 00447951966260 😹
- Website : www.synergyequipment.comEmail : ram@synergyequipment.comFor Sale : info@synergyequipment.com

