

CAVIBLASTER SY-0625-DE



Diesel Engine with Electric Start, 6 gpm & 2,500 psi

Specifications and Options

Designed as a dependable & durable, yet lightweight and flexible solution for the low budget cleaning operations, the 0625-DE has proven to be a great first step into cavitation

Accessories Included:

Feed Hose (15 feet) with electrical feed pump, Unbalanced Gun, High Pressure Hose (50 feet) and Battery Start Optional Accessories:

Aditional pressure hose available in 50 ft or 100 ft sections Max. Pressure hose length recommended up to 300 ft (100 meters) total























CAVIBLASTER SY-0625-DE



SKID Dimensions		
Length w/o handle	27"/69 cm	
Length w handle	33"/84 cm	
Width wheel base	22"/56 cm	
Height	21"/53 cm	
Weight	143 Lbs / 65 Kg	

Pump System		
Pressure Pump	General EZ3045	
Pump Material / Type	Brass / Positive Displacement	
Flow Rate	4.5 gpm / 17.1 Lpm	
Nozzle Pressure	2,500 psi / 172 Bar	
Hose Diam/Max Lgth	3/8" - 300 ft / 100 m	

Tools	
Tool Type	Unbalanced Gun

Drive System	
Engine	Kohler Diesel KD420
Engine Type	4-Stroke
Cooling System	Air
Ignition System	Direct Injection
Lubrication	Full-Pressure w/ filter
Max Output HP/kW	9.1 HP / 6.8 kW
Clutch	Direct Drive
Starting System	Electric Starter

Shipping Dimensions	
Pallet 40x48x36"	240 Lbs Gross weight

Ideal For	
Small to Mid size Boat Hulls	
Piers, Pilings & Seawalls	
Running gear & Out drivers	
Pools & Indoor Underwater Instalations	











SYNERGY INFRASTRUCTURE



CAVIBLASTER SY-0625-DE

Contact us

29th Street, Amman Road, Behind Al Huraiz Est. For Industry, Al Qusais, Industrial Area – 1, Dubai, United Arab Emirates

Website: www.synergyequipment.comEmail: ram@synergyequipment.comFor Sale: info@synergyequipment.com













