

# SY-NUVAIR PRO CO ALARM ANALYZER

Nuvair CO analyzers detect levels of carbon monoxide that could be harmful to a diver before the gas reaches the diver. Our CO analyzers connect in-line with high pressure compressors to monitor tank fills or on low pressure compressors used by surface-supplied divers. Visual and audible alarms warn of potential CO hazards. Depending on your requirements, we have three styles of CO analyzers that can be portable or mounted directly to the compressor.

## FEATURES

- Tank readings through restrictor or in-line monitoring on compressor
- Temperature compensated sensor
- User replaceable battery options
- Low battery warning indicator
- Made to test breathing gases\*\*
- Optional relays for external alarm or compressor control



## SPECIFICATIONS\*

Flow Rate	0.5-5 L/min
Resolution	1 ppm
Repeatability	<+5%
Accuracy	±5%
Sensor Type	Electrochemical
Expected Sensor Life	>24 months in normal use from date of manufacture
Range	0-50 ppm CO
Alarms	Two user-programmable audible and visual alarms
Response Time	<50 seconds over complete temperature range
Operating Temperature	14° to 122°F (-10° to 50°C) continuous -4° to 122°F (-20° to 50°C) intermittent
Operating Humidity	Non-condensing: 15-90% continuous, 0-99% intermittent
Storage Temperature	14° to 140°F (-10° to 60°C)
Power	9 V battery, rechargeable lithium battery, 110/220 V wall plug-in or 12 V DIN rail (panel mount only)
Dimensions	4 x 2 x 5.5 in (10.2 x 5 x 14 cm) panel mount SKU: 9624 2.5 x 1.75 x 4.25 in (6.3 x 4.5 x 10.8 cm) handheld SKU: 9625 3.9 x 8.7 x 7.5 in (9.9 x 22.1 x 19.1 cm) waterproof box SKU: 9626
Weight	9 oz (0.3 kg) panel mount / 7.8 oz (0.22 kg) handheld / 2 lbs 8 oz (1.27 kg) waterproof box
Warranty	12 months from date of purchase, covers parts and labor.


Please note: Never expose gas sensors to pressure or you may cause damage and/or false readings. Damaged sensors will not provide accurate gas analysis. Inaccurate gas analysis can lead to serious personal injury or death. Most gas analyzers can be used to analyze a regulated gas sample flow, the contents of a gas cylinder, or the flow from a regulator. The flow rate of gas must equal .05-5 L/min. To produce this flow, a flow restrictor and regulator may be required.

\*All specifications are at ambient / sea level, 77°F (25°C) and are subject to change without notice.  
\*\*Calibration must be confirmed with calibration CO test gas.






**SY-NUVAIR PRO CO ALARM ANALYZER**

# Contact us

 29th Street, Amman Road, Behind Al Huraiz Est. For Industry,  
Al Qusais, Industrial Area – 1,  
Dubai, United Arab Emirates

 Tel : 009714 2580533   
 Fax : 042516664   
 UAE : 00971505648178   
 UK : 00447951966260 

 Website : [www.synergiequipment.com](http://www.synergiequipment.com)  
 Email : [ram@synergiequipment.com](mailto:ram@synergiequipment.com)  
 For Sale : [info@synergiequipment.com](mailto:info@synergiequipment.com)

