



# SYNERGY

INNOVATIVE DIVING EQUIPMENT TRADING LLC

INSPIRING • ENGINEERING • INNOVATION

UAE • UK • INDIA • AZERBAIJAN



ISO 45001:2018 OHSMS



PRODUCT CERTIFICATE  
EC Attestation of Conformity

In Compliance with following  
Directives:  
Machinery Directive 2006/42/EC

Low Voltage Directive 2014/35/EU

Pressure Equipment Directive  
2014/68/EU



## CORENA S2 P-150 AIR COMPRESSOR OIL



Shell Corena S2 P is high quality air compressor oil designed to deliver the lubrication performance for high pressure reciprocating compressors. It is suitable for most reciprocating air compressors running at up to 220°C discharge temperatures at elevated pressures.

### Performance, Features & Benefits

#### • Long oil life-Maintenance saving

Shell Corena S2 P allows the interval between valve and piston maintenance to be extended under certain applications. Compressors can be kept in service for much longer periods, operating at a consistently high level of efficiency. Extended maintenance capability is supported by resistance to formation of carbon deposits and lacquer on valves and piston crowns at high working temperatures and pressures.

#### • Outstanding wear protection


Shell Corena S2 P helps provide effective protection of internal metal surfaces from corrosion and wear to help prolong the life of critical parts such as bearings and pistons.

#### • Maintaining system efficiency

Shell Corena S2 P helps prevent the formation of carbon deposits and lacquer on valves and piston crowns at high working temperatures and pressures. These can cause serious damage, lower compressor efficiency and increase maintenance costs. In addition, Shell Corena S2 P has good water separation to help prevent accelerated corrosion, facilitating easy condensate draining.

#### • Enhanced air line safety

In discharge air-lines, the combination of rust particles, dispersed in carbonaceous deposits, coupled with heat from recently compressed air, can cause a reaction leading to the possibility of fires and explosion. Shell Corena S2 P helps to minimise the likelihood of this danger.





## CORENA S2 P-150 AIR COMPRESSOR OIL

### Main Applications

- **Reciprocating air compressors**

Shell Corena S2 P is suitable for use in industrial reciprocating air compressors operating with air discharge temperatures of up to 220°C.

- **Breathing air compressors**

Shell Corena S2 P may be used in breathing air compressors, provided subsidiary clean-up apparatus is used to ensure that the air produced is fit for breathing.

### Specifications, Approvals & Recommendations.

- DIN 51506 VDL
- ISO 6743-3A-L DAA Normal Duty
- ISO 6743-3A-L-DAB

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.


### Compatibility & Miscibility

- **Seal Compatibility**

Shell Corena S2 P oils are compatible with all sealing materials commonly used in air compressors.

## Typical physical characteristics

Properties			Method	Corena S2 P 150
ISO Viscosity Grade			ISO3448	150
Kinematic Viscosity	@40°C	mm <sup>2</sup> /s	ASTM D445	155
Kinematic Viscosity	@100°C	mm <sup>2</sup> /s	ASTM D445	12.1
Density	@15°C	kg/m <sup>3</sup>	ASTM D1298	902
Flash Point (COC)			ASTM D92	240
Pour Point			ASTM D97	-30
Neutralisation Value			ASTM D974	0.3
Sulphated Ash			DIN 51575	0.06
Oxidation Stability (delta CCR)			DIN 51352-2	2.3
Properties Of The Distillation Residue (20%) - Carbon Residue (C)			DIN 51551	0.3
Properties Of The Distillation Residue (20%) - Kinematic Viscosi	@40°C	mm <sup>2</sup> /s	DIN 51562	280
Rust Prevention - Synthetic Sea Water			ASTM D665B	Pass
Water Separability	@54°C	min	ASTM D1401	-
Water Separability	@82°C	min	ASTM D1401	20



## CORENA S2 P-150 AIR COMPRESSOR OIL

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in @82°C these characteristics may occur.

### Health, Safety & Environment.

#### • Health and Safety

Shell Corena 52 P is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained. Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water. Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.epc.shell.com/>

#### • Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

### Additional Information

#### • Advice

Advice on applications not covered here may be obtained from your shell representative.



# SYNERGY

INNOVATIVE DIVING EQUIPMENT TRADING LLC

INSPIRING • ENGINEERING • INNOVATION

UAE • UK • INDIA • AZERBAIJAN



PRODUCT CERTIFICATE  
EC Attestation of Conformity  
  
In Compliance with following Directives:  
Machinery Directive 2006/42/EC  
Low Voltage Directive 2014/35/EU  
Pressure Equipment Directive 2014/68/EU



## CORENA S2 P-150 AIR COMPRESSOR OIL

## Contact us

29th Street, Amman Road, Behind Al Huraiz Est. For Industry,  
Al Qusais, Industrial Area - 1,  
Dubai, United Arab Emirates

- Tel : 009714 2580533
- Fax : 009714 2580534
- UAE : 00971505648178
- UK : 00447951966260

- Website : [www.synergiequipment.com](http://www.synergiequipment.com)
- Email : [ram@synergiequipment.com](mailto:ram@synergiequipment.com)
- For Sale : [info@synergiequipment.com](mailto:info@synergiequipment.com)

