


COMPLETE UNDERWATER VIDEO SYSTEM SY-UWS-3310-DC



- Complete portable ac/dc video system
- Light weight
- Sd dvr
- Led light

Standard system includes:
 ·UWC-325/p: Fixed focus, color camera
 ·UWL-401: Led light
 DHM-60: Bracket

•C-2303-100M: 330 ft. cable
 CON-3300/DC: 15" lcd monitor,
 Sd/dvr recorder, power supply
 With variable light control.
 All mounted in a weather-
 Resistant shipping case



COMPLETE UNDERWATER VIDEO SYSTEM SY-UWS-3310-DC

Mechanical	Specification
Weight	6 oz (.2kg) Dry, 3 oz(.06kg) wet
Depth Rating	2000 ft (600m)
Housing	Black delrin
Electrical	
Image Device	1/3" CCD sensor (412k pixel)
Sensitivity	.001 lux @f1.4
Resolution	600 TV lines standard
Video Out	1.2 Vpp
Power	12 VDC @ 110 ma.
Optical	
Lens	3.6mm, Electronic-Iris
Focus	Fixed 4" to infinity
Angle of View	70 horz. (in water)



PART NO : SY-UWC-325/p/e



PART NO : SY-UWL-401

Mechanical	Specification
Weight	7oz(0.2kg) Dry, 3 oz.(.1kg) Wet
Depth Rating	2000 ft (600m)
Housing	6061-16 Anodized Aluminium
Electrical	
Power	12 VDC @ 110 ma.
Wattage	18 watt (Eq to 150 watt halogen)
Output	700 lux at 1 meter
Optical	
Lens	3.6mm, Electronic-Iris
Focus	Fixed 4" to infinity
Angle of View	70 horz. (in water)

Mechanical	Specification
Conductors	16ea #22 awg 1 RG-59 Coax
Length (mtrs)	100/150/200 as per requirement
Diameter	8.5mm (0.35")
Materials	Orange Polyurethane jacket
Breaking Strength	1200 lbs
End fittings	
Diver End	Moulded Y connection
Camera	Rmk-5-fs with locking sleeve
Light	Rmg-3-fs with locking sleeve
Surface end	Soldered connection
Cable	8 pin amphenol connector



PART NO : SY-VC-150M (length)

PART NO : SY-VC-100M (length)

COMPLETE UNDERWATER VIDEO SYSTEM SY-UWS-3310-DC



PART NO : SY-CON-3300DC


ELECTRICAL	Specification
Conductors	16 ea. #22 awg; 1 RG-59 Coax
MECHANICAL	
Length	330 ft. (100m) Standard
Diameter	0.35" (8.9 mm)
Jacket	Polyurethane (orange)
Breaking Strength	1200 lbs. (540 kg)

OPTIONS:




Camera-	<ul style="list-style-type: none"> • Light - uwl-400 led light 1920 lux @ 1m (4300 lumens)
• Uwc-325/ss	@ 3000 k 36 watts
• Optional connectors	• Booster - for cables over 1500 ft. (up to 3000 ft.)
• Cable - user-specified cable lengths	Mounts in console.
• Bracket - hm-300 helmet mount	• Video typewriter, model 6100 - Time/date, multiple pages of text and Digital control of all cameras.

COMPLETE UNDERWATER VIDEO SYSTEM SY-UWS-3310-DC

Contact us

 29th Street, Amman Road, Behind Al Huraiz Est. For Industry,
Al Qusais, Industrial Area – 1,
Dubai, United Arab Emirates

-  Tel : 009714 2580533 
-  Fax : 042516664 
-  UAE : 00971505648178 
-  UK : 00447951966260 

-  Website : www.synergiequipment.com
-  Email : ram@synergiequipment.com
-  For Sale : info@synergiequipment.com

