













The **DS11** Diamond Chain Saw is specifically designed to cut solid concrete underwater. Cuts square corners without over-cut and can plunge cut sea walls up to 18" thick. Two available bar lengths (15" and 18") and two different chains depending on the amount of rebar and hardness of the concrete.

A minimum of 20 PSI water pressure is required at the saw for cooling and lubrication of the bar and chain. Painted hi-visibility yellow.

FEATURES

- Direct drive motor no chain coast when trigger is released
- Integral Stanley Hyrevz gear motor for durability and power
- Trigger activated water to bar and chain for lubrication
- · Multi position trigger handle and Wall Walker reduces diver fatigue
- Heavy duty cast aluminum
- Cut steel reinforced concrete with Pinnacle chain
- Stainless Steel spool and fasteners
- Interlocking safety trigger and hand guard
- Pinnacle Chain: For Steel Reinforced, Heavy Aggregate Concrete
- Ultra Chain For Light Wire Mesh, Soft/Green Concrete
- Order bar and chain separately See Chart for Selection















SPECIFICATIONS

15 or 18" / Capacity

38 or 45 cm Bar

Chain Type Diamond Impregnated Chain

Segments

Circuit Type Open Center

Flow Range 12 gpm / 45 lpm

Working Pressure 1000-2000 psi / 70-140 bar

Full Relief Settin 2250 psi / 155 bar

Weight

(less bar & chain) 28 lbs / 12.7 kg

Length 37 or 40" / 99 or 101.6 cm

(with bar & chain)

Width 9" / 23 cm

Couplers Yes

Hose Whips Yes (1/2" NPT Male Thread)

Lubrication/Cooling Internal Water Channels in Bar













The chart below will assist in chain selection for balance of cutting performance and chain life

Aggregate	Extra Hard		Hard	Mediu	ım		Soft	Abrasive
Material	Chert	Basalt	Granite River	. Marb	le	Sandstone	9	Masonry, Brick, Block,
	Flint	Quartz	Rock	Limesto	one			Green Concrete
Approximate	0	0	ZVATIV	E UI	VII	V	2	
Moh's Scale	9	8	NIG 8	6	5	4	3	
Reinforcing		Lots of	Steel		S	ome Steel	1/2	
Steel	1" Dou	ble Mat	Single Mat	#5 #	‡4 ‡	#3 Wire M	esh	

Saw Chain Wear (in-ft)

Pinnacle-32	150 in-ft	600-800 in-ft	2000 in-ft	
Pinnacle-39	150 111-11	000-000 111-11	2000 111-11	
Ultra-32	Щ	2000 in ft	M. A. C.	1500 in ft
Ultra-37		2000 in-ft		1500 in-ft

ORDERING INFORMATION

PART NUMBER

Diamond Chain Saw, Underwater, No Bar & Chain Ds115000 Order Bar and Chain Separately Below


















ACCESSORIES				
30305	15" Bar, Sprocket Nose			
56801	15" Diamond Chain, Ultra 32			
56803	15" Diamond Chain, Pinnacle, 32			
30306	18" Bar, Sprocket Nose			
56802	18" Diamond Chain, Ultra 37			
58632	18" Diamond Chain, Pinnacle, 37			
03971	Flush-Face Coupling Set, 3/8" NPT			
03974	Flush-Face Coupling Set, ½" NPT			
06830	Hose Whip 18" long, -8 SAE x ½" NPT			
23517	Sprocket Wrench			
31848	Dual Hose, 50' x ½", with couplers			
31972	Dual Hose, 25' x ½", with couplers			
58633	Twinned Hose, 25' x ½", with couplers			
58634	Twinned Hose, 50' x ½", with couplers			
20859	Diamond Chain Butterfly Repair Kit			
20857	Chain Repair Spinner			
20858	Chain Repair Breaker			
DCP30101	Water Pump, 12 VDC, Battery Clip			
DCP30100	Water Pump, 12 VDC, Marine Type Plug			

When hydraulic hose exceeds 100' (30.4 m) in length, increase I.D. of both pressure and return hose. For more information, consult Stanley Hydraulic Tools

ACCESSORIES

To fill out a Product Warranty Recording form and for information on your warranty visit stanleyhydraulic.com and select the Warranty tab.



















Contact us

29th Street, Amman Road, Behind Al Huraiz Est. For Industry, Al Qusais, Industrial Area - 1, Dubai, United Arab Emirates

: 009714 2580533

Fax: 042516664

UAE: 00971505648178

UK: 00447951966260

Website: www.synergyequipment.com

: ram@synergyequipment.com

For Sale: info@synergyequipment.com

