













SPECIFICATIONS		
Capacity	9" / 23 cm Wheel	
Spindle	%" - 11 Threaded	
Circuit Type Open Center		
Flow Range	4-12 gpm / 15-45 lpm	
Working Pressure	1000-2000 psi / 70-140 bar	
Full Relief Setting	2250 psi / 155 bar	
RPM	3200 @ 12 gpm / 45 lpm	
Weight (with guard)	15 lbs / 6.8 kg	
Length	11" / 28 cm	
Width (with guard)	10¼" / 26 cm	
Hydraulic Ports	-8 SAE O-ring	
Connection Size and Type	%" Male Pipe Adapter	
Couplers	Varies with model (See Ordering Information)	
Hose Whips	No (See Accessories)	

FEATURES

- Integral Stanley Hyrevz gear motor produces high torque
- Stainless Steel spools and fasteners
- Two position assist handle for right/left hand operation
- · Oversized trigger with guard for diver comfort
- Adjustable wheel guard for infinite positions
- · Plastisol covered handle for comfortable ergonomic grip
- · Use with grinding wheels, hull scrubbing brushes, wire and nylon brushes, barnacle busters and Desmond wheels

3200 rpm @ 12 gpm

Cast-in lifting eye

















ORDERING INFORMATION

PART NUMBER


GR29310 Grinder, Underwater, less couplers GR2930101 Grinder, Underwater, couplers, CE

ACCE	SSORIES
03971	Flush-Face Coupling Set, %" NPT
03974	Flush-Face Coupling Set, ½" NPT
06830	Hose Whip 18" long, -8 SAE x 1/2" NPT
02587	Grinding wheel for metal, 9" diameter x % - 11 thd
02588	Grinding wheel for masonry, 9" diameter x % - 11 thd
03691	Grinding wheel, 7" diameter x % - 11 thread
05194	Adapter, % - 11 thread, depressed center wheel
31848	Dual Hose, 50' x ½", with couplers
31972	Dual Hose, 25' x ½", with couplers
58633	Twinned Hose, 25' x 1/2", with couplers
58634	Twinned Hose, 50' x ½", with couplers

When hydraulic hose exceeds 100' (30.4 m) in length, increase I.D. of both pressure and return hose. For more information, consult Stanley Hydraulic Tools.

MPORTANT

To fill out a Product Warranty Recording form and for information on your warranty visit stanleyhydraulic.com and select the Warranty tab.



Note: The warranty recording form must be submitted to validate the warranty.

















•	Description Application Materials Part Number Size Max Rating	9" All-Cut Diamond Grit Cutting Disc Durable, Long Life with ability to cut wide range of materials General Cutting / Various Materials All Purpose, Concrete, Stone, Steel & Alloys, Composite, PVC, Wood AC230-22 230mm x 3.1mm 6,600rpm (80 m/s)		
•	Description Application Materials Part Number Size Max Rating	General Grinding / Various N	ty to grind wide range of materials	
•	Description Application Materials Part Number Size Max Rating	7" & 9" Diamond Cutting Top Performance, long life Cutting Concrete, Sandstone, Const 322633 180mm x 2.6mm 8,500rpm (80 m/s)		Dicocu
•	Description Application Materials Part Number Size Max Rating		d Abrasive Grinding Disc for Metal ormance, minimal vibration & long life olid and Plate GW978DCS 230mm DPC x 6.4mm 6,600rpm (80 m/s)	
•	Description Application Materials Part Number Size Max Rating		d Abrasive Cutting Disc for Metal ormance, minimal vibration & long life d and Plate CW978DCS 230mm DPC x 2.5mm 6,600rpm (80 m/s)	













		7" & 9" Diameter Bonded Abrasive Grinding Disc for Stone		
•	Description	Depressed Centre High performance, minimal vibration & long life		
•	Application	Grinding Masonry, Stone, Concrete		
•	Materials	Stone, Brick, Concrete, Ceramics		
•	Part Number	GW778DCM GW978DCM		
•	Size	180mm DPC x 6.4mm 230mm DPC x 6.4mm		
•	Max Rating	8,500rpm (80 m/s) 6,600rpm (80 m/s)		
		9" Diameter Bonded Abrasive Cutting Disc for Stone		
•	Description	Depressed Centre High performance, minimal vibration & long life		
•	Application	Cutting Masonry, Stone, Concrete		
•	Materials	Stone, Brick, Concrete, Ceramics		
•	Part Number	CW978DCM		
•	Size	230mm DPC x 3.2mm		
•	Max Rating	6,600rpm (80 m/s)		
		9" Diameter Bonded Abrasive Grinding Disc for Metal		
		5/8-11 thread Spin-On		
•	Description	Excellent material removal and long life		
•	Application	Grinding Pipe, Structural, Solid and Plate		
•	Materials	Steel, Stainless Steel		
•	Part Number	GW49105S		
•	Size	230mm x 6mm x 5/8-11		
•	Max Rating	6,600rpm (80 m/s)		
		9" Diameter Bonded Abrasive Cutting Disc for Metal		
		5/8-11 thread Spin-On		
•	Description	Excellent material removal and long life		
•	Application	Cutting Pipe, Structural, Solid and Plate		
•	Materials	Steel , Stainless Steel		
•	Part Number	CW48983S		
•	Size	230mm x 4mm x 5/8-11		
•	Max Rating	6,600rpm (80 m/s)		















	Cup Wire Brush 125mm Crimped Steel Bristles	
 Description Application Materials Part Number Size Max Rating 	General purpose cup wire brush Surface preparation, Rust removal, Cleaning Various, Inc: Steel, Stainless Steel & Glass Fibre CWB125-CB58 125mm x 5/8-11 threaded bore 6,500rpm	
	Cup Wire Brush 100mm Twisted Knot Steel Bristles	
 Description Application Materials Part Number Size Max Rating 	Hard wearing cup brush with good material removal De-burring, De-scaling, Marine growth removal, Paint removal Various, Inc: Steel, Stainless Steel & Glass Fibre CWB100-TK58 100mm x 5/8-11 threaded bore 8,500rpm	
- Wax racing	Bevel Wire Brush 115mm Twisted Knot Steel Bristles	9 6
 Description Application Materials Part Number Size Max Rating 	Hard wearing bevel brush with good material removal De-burring, De-scaling, Marine growth removal, Paint removal Various, Inc: Steel, Stainless Steel & Glass Fibre BWB115-TK58 115mm x 5/8-11 threaded bore 12,500rpm	
 Description Application Materials Part Number Size Max Rating 	Nylon Brush Nylon Brush Marine growth removal, Cleaning & Polishing Various, Inc: Steel, Stainless Steel & Glass Fibre NB160 160mm 3,200rpm (44 m/s)	
DescriptionApplicationPart NumberSize	Adaptor for NB160 Nylon Rotary Brush Aluminium mount for rotary nylon brush Adaptor for NB160 (above) NB160ADP 5/8-11 threaded bore	

















		7" Rapid Strip Disc DPC, Xtra Coarse, Long Lasting			
•	Description Application Materials Part Number Size Max Rating	Synthetic fibres and coarse ceramic alumina grain Rust & Paint removal. Surface Preparation Various, Inc. Steel, Stainless Steel & Glass Fibre RSD03920 180mm DPC 8,000rpm (75 m/s)			
		7" Rapid Strip Disc D	PC, Xtra Coarse, STD	Density	and the same
•	Description Application Materials Part Number Size Max Rating	Synthetic fibres and coarse silicon carbide grains Light Marine Growth, Rust & Paint removal. Surface Preparation Various, Inc. Steel, Stainless Steel & Glass Fibre RSD85750 180mm DPC 6,700rpm (63 m/s)			
		7" Rapid Strip Disc DPC, Xtra Coarse, Harder Density			
•	Description Application Materials Part Number Size Max Rating	Synthetic fibres and coarse silicon carbide grains Light Marine Growth, Rust & Paint removal. Surface Preparation Various, Inc. Steel, Stainless Steel & Glass Fibre RSD09586 180mm DPC 8,000rpm (75 m/s)			
		7" Conical Fibre Disc (40/80/120 Grit) DPC			
•	Description Application Materials Part Number Size	Zirconium, excellent mande ldeal for edge grinding, Steel, Stainless steel CFD02341 180mm DPC 40-Grit		_	
•	Grit Max Rating	40-Grit 80-Grit 120-Grit 8,500rpm (80 m/s) 8,500rpm (80 m/s)			



















SPECIFICATIONS		
Outside Diameter	150mm (6")	
Recommended Speed	1,000 to 2,000 rpm	
Max Rated Speed	3,200 rpm	
Fitting	5/8-11 Arbour	
Cutting Heads	7 per unit	
Main Body Material	Stainless Steel	

Features and Benefits

Removes heavy build-up of mussels, barnacles or other encrustations from steel, concrete, pilings, seawalls, bulkheads and ships easily.

It is a stainless steel one piece aircraft quality housing stainless steel blocks on the outside diameter and fits a 5/8"-11 shaft. (Other fittings and mounts also available).

Furnished with sharp tooth toolsteel cutters as standard, with builtin safety guard and balanced design for easy operation.

As the unit moves across the surface, the outside blocks shatter barnacles and other heavy growth. The rotating hardened steel cutters follow up with a chipping and scraping action which removes the

remaining material, leaving a clean surface. Water passing through the tool keeps the cutting wheels clean

The rotary action displaces water thus creating a vacuum under the unit. This results in the unit being pressed and held against the ship or work surface. Slight pressure on either side of the tool allows the operator to guide it in any direction.

The tool is ecologically safe since it adds no harmful chemicals to our environment.

A speed of 1000 rpm to 2000 rpm is suggested for underwater use. See over page for hydraulic flow vs shaft speed graph.

Applications include:

Paint removal Ship hulls & rudders Offshore wind turbines **Bridges Pilings** Marine structures Harbour structures Storage tanks















ORDERING INFORMATION

MODEL/PART No. DESCRIPTION

HOP50830

Barnacle Basher 150mm (6") Heavy duty unit with quick change cutter sets


WARRANTY

All tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. We reserve the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

ACCESSORIES

PART No.	DESCRIPTION
50631	Quick Change Cutter Set for 50830 Unit (Set of 7)
50684	Axles (Set of 7) for all 150mm (6") Units





Shaft Speed






























ITEM#	PART#	QTY	DESCRIPTION	
		- 	DESCRIPTION	
2	00026 00166	2	O-RING * RETAINING RING	
3	00186	4	CAPSCREW	
4	00230	2	LOCKWASHER	
5	00231	1	ROLL PIN	
6	00285	1	SETSCREW	
7	00599	1	SETSCREW (GR2930101 ONLY)	
8	00599	1	RETAINING RING EXTERNAL	
9	00072	' 1	CAPSCREW	
10	00936	2	ADAPTER	
11	01211	2	O-RING *	
12	01211	1	GREASE FITTING 1/8 CAPPED	
13	01870	8	CAPSCREW	
14	03972	1	COUPLER,3/8FEM. 3/8NPT	
14	03972		FL.FACE SET 03971	
15	03973	1	COUPLER,3/8MALE 3/8NPT FL.FACE SET 03971	
16	06533	1	O-RING *	
17	07724	2	NYLOCK NUT	
18	07987	1	BACK-UP WASHER	
19	07988	1	COMPRESSION COIL SPRING	
20	07989	1	IDLER GEAR ASSY (INCLUDES DU BUSHING)	
21	07991	1	IDLER SHAFT	
22	08002	1	REVERSING SPOOL	
23	08015	2	BACK-UP RING *	
24	08017	1	O-RING *	
25	08023	1	O-RING *	
26	08130	1	HANDLE	
27	09275	1	RETAINING RING EXTERNAL	
28	09396	1	BACK-UP RING *	
29	11206	1	CIRCUIT TYPE "C" STICKER	
30	11937	1	WHEEL GUARD	
	08322	1	WHEEL GUARD U/W MODEL	
31	12283	1	TRIGGER U/W	
32	12285	1	TRIGGER GUARD U/W	
33	12290	1	CLAMP SCREW	
34	12291	1	THUMB PLATE	
35	12470	1	CAPSCREW	
36	12535	1	CIRCUIT TYPE "E" STICKER	
37	12786	1	STUD	
38	12815	1	WHEEL NUT SPANNER	
39	13783	1	DRIVE GEAR	
40	13789	1	MOTOR CAP ASSY (INCLUDES DU BUSHING & DOWEL PIN)	

ITEM#	PART#	QTY	DESCRIPTION
41	13790	1	BEARING CARRIER
42	13791	1	SPINDLE SHAFT
43	13796	2	DEAD HANDLE BRKT WELDMENT
44	13812	1	ROTARY SHAFT SEAL *
45	13813	1	BALL BEARING
46	13828	1	WOODRUFF KEY #404
47	16495	1	HUB NUT (GR2930101 ONLY)
48	17061	1	VALVE KEEPER
49	22063	1	SPOOL CAP
50	22064	1	ROD WIPER *
51	23678	1	HEADED PUSH PIN
52	28322	1	STICKER "CE" 25MM
53	28409	1	COMPOSITE STICKER
54	28913	1	DRIVE FLANGE (GR2930101 ONLY)
55	73041	1	ON/OFF VALVE SPOOL (NOTE: SEE PAGE 18 BEFORE ORDER- ING)
56	73311	1	MAIN HOUSING ASSY (INCLUDES DU BUSHING) (NOTE: SEE PAGE 18 BEFORE ORDERING)
57	73684	1	NAME TAG - GR29 UW
58	74818	1	INFORMATION TAG - GR2930101
59	13779	1	JAM NUT (INCLUDED WITH GR29310 ONLY)
	16969	1	SEAL KIT

^{*} DENOTES PART IN SEAL KIT















Contact us

29th Street, Amman Road, Behind Al Huraiz Est. For Industry, Al Qusais, Industrial Area - 1, Dubai, United Arab Emirates

: 009714 2580533

Fax: 042516664

UAE: 00971505648178

UK: 00447951966260

Website: www.synergyequipment.com

: ram@synergyequipment.com

For Sale: info@synergyequipment.com

