



UNDERWATER HYDRAULIC HAMMER DRILL SY-HD45310



The Stanley Hydraulic HD45 Hammer Drill is a heavy duty underwater model designed for drilling in concrete, rock and masonry.



The feathering on/off valve and adjustable rotation speed allows easy drill bit start-up and precise control. The high torque rotation motor drives standard 736 Skil hex carbide tipped drill bits and is capable of drilling a 2" diameter hole up to 29" deep. Fluted drill bits require no water or air to clear holes. Ideal for drilling holes for setting anchor bolts. Painted hi-visibility yellow.

SPECIFICATIONS

Chuck Capacity	Up to 2" diameter or 4" core bit
Steel Capacity	736 Skil hex
Circuit Type	Open Center
Flow Range	7-9 gpm / 26-34 lpm
Optimum Flow	8 gpm / 30 lpm
Working Pressure	1500-2000 psi / 105-140 bar
Full Relief Setting	2250 psi / 155 bar
Rotation Speed	0 - 300 rpm
Weight (less tool bit)	49 lbs / 22.2 kg
Length	24½" / 62.2 cm
Width (at handles)	14" / 35 cm
Hydraulic Ports	-8 SAE O-ring
Couplers	Varies with model (See ordering information)
Hose Whips	Yes (¾" NPT Male thread)

FEATURES

- T-Handle with large on/off trigger for precise control
- Stainless Steel spools and fasteners
- Forward-Reverse with adjustable bit rotation speed
- Feathering on/off valve allows easy start and control
- Uses 736 Skil fluted carbide tipped drill bits - requires no water/air to clear holes
- Drills ¾" to 2" diameter holes up to 29" deep and core drills up to 4" in diameter
- Operates in any position
- Trouble free drill steel latch retainer



UNDERWATER HYDRAULIC HAMMER DRILL SY-HD45310

ORDERING INFORMATION

PART NUMBER

- HD45310** Hammer Drill, Underwater, less couplers
- HD4531001** Hammer Drill, Underwater, CE, Trigger Lock, with couplers

ACCESSORIES

- 03971** Flush-Face Coupling Set, 3/8" NPT
- 03974** Flush-Face Coupling Set, 1/2" NPT
- 31848** Dual Hose, 50' x 1/2", with couplers
- 31972** Dual Hose, 25' x 1/2", with couplers
- 58633** Twinned Hose, 25' x 1/2", with couplers
- 58634** Twinned Hose, 50' x 1/2", with couplers
- 02280** Carbide Bit, 3/4" x 24" OAL
- 05163** Carbide Bit, 7/8" x 24" OAL
- 02281** Carbide Bit, 1" x 24" OAL
- 02282** Carbide Bit, 1 1/4" x 24" OAL
- 05167** Carbide Bit, 1 1/2" x 24" OAL
- 02283** Carbide Bit, 2" x 24" OAL
- 04668** Carbide Bit, 1" x 18" OAL
- 04896** Carbide Bit, 1 1/4" x 36" OAL
- 27902** Percussion Core Bit, 2 1/2" diameter x 6" OAL (part #30279 required)
- 27904** Percussion Core Bit, 3" diameter x 6" OAL (Part #30279 required)
- 30279** HD45 (Skil 736) Adapter

When hydraulic hose exceeds 100' (30.4 m) in length, increase I.D. of both pressure and return hose. For more information, consult Stanley Hydraulic Tools.

IMPORTANT


To fill out a Product Warranty Recording form and for information on your warranty visit stanleyhydraulic.com and select the Warranty tab.






Note: The warranty recording form must be submitted to validate the warranty.

UNDERWATER HYDRAULIC HAMMER DRILL SY-HD45310

Contact us

 29th Street, Amman Road, Behind Al Huraiz Est. For Industry,
Al Qusais, Industrial Area – 1,
Dubai, United Arab Emirates

-  Tel : 009714 2580533 
-  Fax : 042516664 
-  UAE : 00971505648178 
-  UK : 00447951966260 

-  Website : www.synergiequipment.com
-  Email : ram@synergiequipment.com
-  For Sale : info@synergiequipment.com

